#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

### (19) World Intellectual Property Organization International Bureau



# 

#### (43) International Publication Date 28 July 2005 (28.07.2005)

#### PCT

### (10) International Publication Number WO 2005/068039. A1

[DK/DK]; Brødeskovparken 33, DK-3340 Hillerød (DK).

kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,

(74) Common Representative: HALDOR TOPSØE A/S;

(81) Designated States (unless otherwise indicated, for every

Nymøllevej 55, DK-2800 Kgs. Lyngby (DK).

(51) International Patent Classification7: 3/20, B01J 8/04

B01D 3/26,

(72) Inventor; and (75) Inventor/Applicant (for US only): BREIVIK, Rasmus

(21) International Application Number:

PCT/EP2004/014485

(22) International Filing Date:

20 December 2004 (20.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

PA 2004 00040


15 January 2004 (15.01.2004) DK

> (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

> > [Continued on next page]

(71) Applicant (for all designated States except US): HAL-DOR TOPSØE A/S [DK/DK]; Nymøllevej 55, DK-2800 Kgs. Lyngby (DK).

(54) Title: VAPOUR-LIQUID DISTRIBUTION TRAY



Liquid-vapour distribution (57) Abstract: device for use in two-phase concurrent down-flow vessels, comprising: horizontal tray being perforated with holes, each perforation through the horizontal tray being fitted with a vapour lift tube, the vapour lift tube consists of at least one elongated up-flow leg and one down-flow leg creating at least one up-flow zone and a down-flow zone between the up-flow zone and down-flow zone, the improvement of which comprises a bluff body being arranged within the transition zone and/or in a region of the up-flow or down-flow zone adjacent to the transition zone of the vapour lift tube.

## WO 2005/068039 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

with amended claims and statement

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

#### Published:

with international search report